

# Super Erecta® Hot Shelving

**Shelves that keep food hot, appetizing, and ready-to-go.**

**Flexible Design:** Configure heated holding solutions almost anyway imaginable by combining with other Super Erecta shelving systems to create

- Stand alone heated holding solutions
- Storage solutions with integrated heated holding
- Workstations with integrated heated holding

**Consistent Heat Distribution:** High quality, Type 304 stainless steel construction combined with aluminum inner core for consistent, reliable radiant heat across each shelf. Adjustable thermostat, 200°F (93°C) maximum surface temperature.

**Low Wattage Design:** Requires less power to operate and lower energy consumption.

**Adjustability:** Shelves can be adjusted at 1" (25mm) increments to customize to desired shelf spacing. Compatible with all Super Erecta SiteSelect posts

**Cleanable and Durable:** Smooth corrosion resistant stainless steel surfaces are easy-to-clean and durable to stand up to daily usage.

**Shelf Sizes:** 18 different shelf sizes to choose from.

- 3 depths: 14" (356mm), 18" (457mm), 24" (610mm),
- 6 lengths: 24" (610mm), 30" (762mm), 36" (914mm), 42" (1067mm), 48" (1219mm), 60" (1524mm).

Plastic feet included with every shelf. Posts ordered separately.

**Enclosed Shelf Kits:** Extend holding time with pass-thru enclosure kits that include a heated shelf, non-heated stainless shelf, side panels, hinged doors on control side, and sliding doors on opposite side.

9 sizes to choose from.

- 3 depths 14" (356mm), 18" (457mm), 24" (610mm)
- 3 lengths 36" (914mm), 42" (1067mm), 48" (1219mm).

Posts ordered separately.

**Easy Order Workstations:** 5 pre-configured assembly / prep stations with integrated heated holding to boost operational efficiency. 3 models with an open heated shelf and 2 models with an enclosed heated shelf.

**Warranty:** 2 year parts & labor warranty



Shown as a stand alone counter-top unit with plastic feet.



Shown as a tiered shelving unit.



Shown with heated shelf, enclosure kit and standard Super Erecta shelving.



Heated shelf enclosure kit shown with a Super Erecta workstation.



## Specifications

**Construction:** Type 304 stainless steel exterior surfaces with black epoxy coated corners. Each shelf includes (4) polymer split sleeves to mount to Super Erecta SiteSelect posts (posts sold separately). (4) 3" polymer feet to use on countertop as a heated worksurface.

**Heating System:** Thermostatically controlled, low wattage foil elements adhered to aluminum diffuser to evenly heat the stainless steel surface with hot air. On / Off power switch and thermostat provide separate individual control of every shelf.

**Clearance Requirements:** Minimum clearance from bottom of shelf to combustible surface is 1.5" (38mm). Recommended minimum spacing between shelves is 5.73" (146mm)

### Shelves

Includes shelf, one bag of split sleeves and (4) plastic feet (posts not included). For actual dimensions add 5/8" (16mm) to depth and subtract 1/16" (2mm) from length.



Use with Super Erecta Posts or Countertop Feet



## Replacement Parts & Accessories

Replacement Split Sleeves: **Model # 9985** (bag of 4 sets)




Thermostat Cover: **Model # HS-THERMCOVER**



Replacement Feet: **Model # 3FHS-4PK** (Qty = 4)



Plastic Post Glides: **Model # 9991P** (Qty = 1) For use in countertop applications.



BS 1363  
Approved 13A UK  
Plug British  
Standard 3  
Square Pin AC  
Power Plug

## SiteSelect™ Posts

Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double-grooved every 8" (203mm) for easy identification. Stationary post heights include leveling foot, mobile posts for use with stem casters



Stationary Post

Post for Stem  
Caster

## Stationary Posts

Model No. Chrome	Model No. Stainless Steel	Actual Height		Approx Pkd. Wt.	
		(in.)	(mm)	(lbs.)	(kg)
<b>7P</b>	-	7.375	187	0.5	0.3
<b>13P</b>	<b>13PS</b>	14.375	365	1	0.5
<b>27P</b>	<b>27PS</b>	28.375	720	1.75	0.75
<b>33P</b>	<b>33PS</b>	34.375	873	2	0.9
<b>54P</b>	<b>54PS</b>	54.4375	1382	3	1.4
<b>63P</b>	<b>63PS</b>	62.4375	1585	3.5	1.6
<b>74P</b>	<b>74PS</b>	74.5	1892	4	1.8
<b>86P</b>	<b>86PS</b>	86.5	2197	5	2.3
<b>*96P</b>	-	96.5	2450	5.5	2.5

## Mobile Posts

Model No. Chrome	Model No. Stainless Steel	Actual Height		Approx. Pkd. Wt.	
		(in.)	(mm)	(lbs.)	(kg)
<b>13UP</b>	<b>13UPS</b>	13.75	349	1	0.5
<b>27UP</b>	<b>27UPS</b>	27.75	704	1.75	0.75
<b>33UP</b>	<b>33UPS</b>	33.75	857	2	0.9
<b>54UP</b>	<b>54UPS</b>	53.8125	1366	3	1.4
<b>63UP</b>	<b>63UPS</b>	61.8125	1570	3.5	1.6
-	-	69.75	1771	3.75	1.7
<b>74UP</b>	<b>74UPS</b>	73.875	1876	4	1.8
<b>86UP</b>	<b>86UPS</b>	85.875	2181	4.5	2.0

Depth x Length

(in.)	(mm)	BS-1363 Plug Model No.
14x24	356x610	<b>HSX1424-UK</b>
14x30	356x762	<b>HSX1430-UK</b>
14x36	356x914	<b>HSX1436-UK</b>
14x42	356x1067	<b>HSX1442-UK</b>
14x48	356x1219	<b>HSX1448-UK</b>
14x60	356x1524	<b>HSX1460-UK</b>
18x24	457x610	<b>HSX1824-UK</b>
18x30	457x762	<b>HSX1830-UK</b>
18x36	457x914	<b>HSX1836-UK</b>
18x42	457x1067	<b>HSX1842-UK</b>
18x48	457x1219	<b>HSX1848-UK</b>
18x60	457x1524	<b>HSX1860-UK</b>
24x24	610x610	<b>HSX2424-UK</b>
24x30	610x762	<b>HSX2430-UK</b>
24x36	610x914	<b>HSX2436-UK</b>
24x42	610x1067	<b>HSX2442-UK</b>
24x48	610x1219	<b>HSX2448-UK</b>
24x60	610x1524	<b>HSX2460-UK</b>



Supplied by  **JESTIC**  
FOODSERVICE SOLUTIONS